

## GENERAL INFORMATION

- When installing this product, the pipes must be flushed clean where the product is being installed.
- Always fit isolating taps to the hot and cold inlet connections in accordance with national plumbing code AS3500.
- Ensure the hoses are not twisted or stretched, are not under tension and not bent to a radius less than 25mm when being installed.
- If the water temperature exceeds 80°C an approved water tempering valve must be fitted.
- For domestic use only, not suitable for commercial applications.

## MAINTENANCE

- Clean regularly using mild soap and dry with a soft cloth.
- Do Not use abrasive cleaners or harsh detergents.

### **The warranty will not apply if:**

- The product has been damaged by improper use;
- The product has not been used in accordance with any applicable instruction guide;
- The purchaser has attempted to modify or repair the product;
- The product is not installed by a licenced Plumber.

***Failure to comply with any of the above instructions will void all warranties.***

## INSTALLATION INSTRUCTIONS

1. Place the O Ring Washer over the hole in kitchen where the mixer is to be installed;
2. Fit the mixer body onto the kitchen hole;
3. Place the horseshoe washer on top of the horseshoe plate and fit it onto the mounting bolt using the mounting nut to tighten up the mixer from underneath the kitchen top;
4. Install the flexible hoses now and ensure the flexible hoses are hand tightened into place (DO NOT USE SPANNER TO TIGHTEN AS IT CAN DAMAGE THE O RING). The flexible hoses are to be fitted into the correct inlets for hot water and for cold water (Red band for hot and blue band for cold).
5. It is important to flush out the supply pipes before installing the mixer and connecting the flexible hoses to hot/cold water supply, regardless whether a stop valve and filter have been installed or not. This procedure will stop foreign objects entering the cartridge.